



Sun Control Window Films

Performance Results*:

Visible Light Transmitted	36%
Total Solar Energy Rejected	56%
UV Light Rejected	99%
Glare Reduction	60%
Visible Light Reflected Exterior	20%
Heat Gain Reduction	46%



Neutral 35

A higher standard



RE35NEARL

Neutral 35 Benefits:

- High heat rejection provides energy savings and improved comfort
- Reduces fading and helps to protect furnishings
- Comprehensive 3M manufacturer's warranty
- Reduces glare and eye discomfort
- Increases personal safety from flying glass

Glass Type (All 1/4")	Single Pane Clear	Single Pane Tinted	Double Pane Clear	Double Pane Tinted
Visible Light Transmitted	36%	21%	32%	19%
Total Solar Energy Rejected	56%	61%	49%	61%
UV Light Rejected	99%	99%	99%	99%
Glare Reduction	60%	60%	60%	60%
Visible Light Reflected Exterior	20%	10%	24%	12%
Solar Heat Gain Coefficient	0.44	0.39	0.51	0.39
U Value	0.99	0.99	0.46	0.46
Heat Gain Reduction	46%	38%	27%	23%

*Performance data generated for a typical film on 6mm glass using applicable industry test methods and standards

3M Renewable Energy Division

3M Center, Building 235-2S-27
St. Paul, MN 55144-1000

Printed in U.S.A. © 3M 2011 70-0709-0170-0 (111.5)ii

For color and appearance on our sample cards, no UV Protection or Abrasion Coating has been applied.



The Skin Cancer Foundation recommends this 3M Window Film product as an effective UV protectant.